




# MAG



## WORKING CONDITIONS

Max working pressure \_\_\_\_\_ 10 bar (145 psi)  
 Max working temperature \_\_\_\_\_ 90°C (194°F)  
 Min working temperature \_\_\_\_\_ 4°C (39,2°F)  
 Max total hardness \_\_\_\_\_ 35°F (350 ppm CaCO<sub>3</sub>)

**Remark** - Water treated can be heated up to a max temperature of 90°C, beyond that temperature the conditioning gradually loses its efficacy.

## SPECIFICATIONS

Non-toxic materials, suitable for drinking water.  
 Body MAG MF and MAG MM: CW 614 N brass chromium-plated.  
 Body MAG FF: aluminium.  
 Magnets: neodymium.  
 Magnetic induction: 12.800 GAUSS.

Magnetic conditioning of hard water provides anti-scale protection by making the carbonates unable to deposit and form incrustation on water heaters and pipes, thus reducing energy consumption and prolonging the lifetime of appliances. MAG is a range of magnetic conditioners made of chrome-plated brass and neodymium magnets with magnetic induction up to 12800 gauss.

## MAG MF magnetic anti-scale conditioners

### WITH IN/OUT THREADS MALE/FEMALE

| CODE      | MODEL                            | IN/OUT | DIMENSIONS mm |    |    |
|-----------|----------------------------------|--------|---------------|----|----|
|           |                                  |        | A             | B  | C  |
| RE6115000 | Micro MAG MF                     | 1/8"   | 56            | 30 | 30 |
| RE6115001 | MAG 1 MF complete with two seals | 1/2"   | 57            | 28 | 28 |
| RE6115002 | MAG 2 MF complete with two seals | 3/4"   | 57            | 30 | 30 |

## MAG MM magnetic anti-scale conditioners

### WITH IN/OUT THREADS MALE/MALE

| CODE      | MODEL     | IN/OUT | DIMENSIONS mm |    |    |
|-----------|-----------|--------|---------------|----|----|
|           |           |        | A             | B  | C  |
| RE6115003 | MAG 3 MM  | 1"     | 89            | 50 | 50 |
| RE6115011 | MAG 11 MM | 1"1/4  | 135           | 80 | 80 |
| RE6115012 | MAG 12 MM | 1"1/2  | 135           | 80 | 80 |
| RE6115013 | MAG 13 MM | 2"     | 135           | 80 | 80 |

## MAG FF magnetic anti-scale conditioners

### WITH IN/OUT THREADS FEMALE/FEMALE

| CODE      | MODEL     | IN/OUT | DIMENSIONS mm |    |    |
|-----------|-----------|--------|---------------|----|----|
|           |           |        | A             | B  | C  |
| RE6115103 | MAG 3 FF  | 1"     | 135           | 80 | 80 |
| RE6115111 | MAG 11 FF | 1"1/4  | 135           | 80 | 80 |
| RE6115112 | MAG 12 FF | 1"1/2  | 135           | 80 | 80 |
| RE6115113 | MAG 13 FF | 2"     | 135           | 80 | 80 |

